



LED Panel Light Specification






Product Features

1. Certificate: &UL & DLC & FCC & CE
2. Lifespan > 50,000 hours & 5 years warranty
3. Flicker-free driver,0-10V dimming can be well compatible with most dimmers;
4. Even & uniform light: branded PMMA light guide plate with perfect laser screening and light distribution technology.
5. Use high quality SMD2835 LEDs
6. Aluminum Alloy Frame: strong and firm due to special fabrication processing; frame color can be silver or white
7. Installation: Recessed ; Suspended ; Surface-mounted.
8. Human-friendly Junction driver box for fire-proofing and easy installation.

Product Dimension



Part No.	Size(ft)	Outline Dimension(mm)			
		L	W	H1	H2
WSD-P22FT36W-XXK	2X2 ft	603	603	12	50
WSD-P14FT36W-XXK	1X4 ft	1212	303	12	50
WSD-P24FT40W-XXK	2X4 ft	1212	603	12	50
WSD-P24FT48W-XXK	2X4 ft	1212	603	12	50



Specification



Size	Model	Power	Inputvoltage	Luminous Flux(lm)	Luminous Efficacy (lm/W)	Color temperature	(Ra)	beam angle	Lifespan	Dimmable
2X2ft	WSD-P22FT36W-XXK	36W	AC100-277V	4765.99lm	133.09	4000K, 5000K	80	120	>50000	0-10V
1X4ft	WSD-P14FT36W-XXK	36W		4775.26lm	134.22	4000K, 5000K	80	120	>50000	
2X4ft	WSD-P24FT40W-XXK	40W		5060.63lm	132.82	4000K, 5000K	80	120	>50000	
2X4ft	WSD-P24FT48W-XXK	48W		6378.95lm	132.62	4000K, 5000K	80	120	>50000	

Accessories



Emergency Kits		Charging: 24hours	Surface Mounting Kits		Hanging Kits	
		Back up: 90minutes				
		Power: 6Watts				

Application









Test Report



WSD-P22FT36W-XXK









Test Report



WSD-P24FT40W-XXK







Spectroradiometric Parameters



Test Report ■ ■ ■

WSD-P24FT48W-XXK





Packing /weight

Model	Carton Size (L*W*H)mm	Carton CBM m ³	QTY PCS	Single N.W. KG	FCL G.W. KG	20GP PCS	40GP PCS	40HQ PCS
2X2ft	710x710x130	0.065533	2	4.2	9.26	858	1770	2076
1X4ft	1310x410x130	0.069823	2	4.2	9.26	802	1662	1948
2X4ft	1310x710x130	0.120913	2	6.8	16.8	464	960	1124

Package Diagram

